## A Typical Mid-block TCP for Bicycle Cycle Track Closure.

1

*The standard clear space for two-way (cycle track) is ten feet ( 10' ), and for one-way bicycle lane is five ( 5' ).*

*SHOW North DIRECTION*

STREET 2

ROAD WORK AHEAD

RIGHT LANE CLOSED AHEAD

LANE SHIFT

*The case when Bicycle Cycle Track is diverted through adjacent travel lane.*

*The spacing between channelizing devices for Bicycle Cycle Track taper shall not exceed 5ft.*

Work Zone

PRIMARY STREET

PARKING LANE

*Show Location and Dimensions of the Work Zone.*

*Specify duration of work.*

LANE SHIFT

END ROAD WORK

STREET 1

**STANDARD NOTES**

PARKING IS TO BE RESTRICTED 72HRS. IN ADVANCE UNLESS THERE IS AN EMERGENCY. SIGNS SHALL BE INSTALLED PRIOR TO THE COMMENCEMENT OF ALL WORK AND REMOVED IMMEDIATELY AFTER COMPLETION OF ACTIVITIES. IF A SIGN IS NO LONGER REQUIRED IT WILL BE REMOVED.

ALL TRAFFIC CONTROL DEVICES INCLUDING SIGNS SHOULD COMPLY WITH NCHRP - 350 CRASH TESTING STANDARDS AND SHOULD HAVE MARKINGS OF COMPLIANCE ON THE STANDARDS. ALL TEMPORARY SIGNS SHALL BE PLACED IN AN APPROPRIATE PLACES, BE ADEQUATE FOR EXISTING STREET CONDITIONS, INCLUDING SIGN DIMENSIONS, AND BE STABLE AND FIRMLY INSTALLED. (The small size of warning signs may be used wherever necessary for providing adequate and safe access for pedestrians within public space).

THE SPACING OF TRAFFIC CONES IS TO BE A MAXIMUM OF 10 '(Ft.).

IN CASE OF ONE WAY ROADWAY OMIT OPPOSITE SIGNAGE (HAVE SIGNS ON BOTH SIDES OF ROADWAY APPROACHING WORK AHEAD).

*The spacing between channelizing devices for Bicycle Cycle Track parallelhttps://wtop.com/dc/2018/12/shot-*

**(Mid-Block , where the Work Zone 100 feet or more from an intersection )**

**LEGEND**

- Traffic Direction;
- Work Zone; (Work Zone)
- Sign Stand Location;
- Traffic Drums or Cones;
- Arrow Board ;
- Construction Truck;
- Retroreflective Delineators (For typical protected bike lanes );
- Temp bicycle direction.

| SPEED (MPH) | MINIMUM SIGN SPACING (FT) |
|---|---|
| 25 | 150 |
| 30 | 200 |
| 35 | 250 |
| 40 | 350 |
| 45 | 550 |
| 50 | 600 |
| 55 | 700 |

*Designed by: L. G. PETROSIAN*